

IMPERIAL AXINSTER*













Please note: There may be slight color difference between the picture and actual carpet.



IMPERIAL AXMINSTER - 33716/138 NIGHT SKY Pin Si Restaurant @ Yishun, Singapore



3716/118 CLARET

3716/138 NIGHT SKY





3716/248 PINE

IMPERIALAXMINSTER

IMPERIALAXMINSTER



3716-118 CLARET



3716-138 NIGHT SKY



3716-248 PINE

IMPERIAL AXMINISTER Specifications

Construction Yarn Composition Pile Weight **Total Weight** Pile Height Total Height Pitch Rows Pattern Repeat Standard Roll Size

Gripper Axminster 80% Pure New Wool, 20% Nylon Ca. 1300 g/m² (38 oz/yd²) Ca. 2230 g/m² (66 oz/yd²) Ca. 8.5 mm (+/- 0.5 mm) Ca. 10.5 mm (+/- 0.5 mm) 7 inch 8 inch 1 m x 1 m 4 m x 30 m

10 (AATCC-175-1993)

Pass - Class II (ASTM-E-648) Pass (DOC FF-1-70)

Self-extinguishing (ASTM-D-2859)

Pass - Max. 450 (ASTM-E-662)

Excellent - 5 (AATCC-16E)

Excellent - 5 (AATCC-165) Excellent - 5 (AATCC-129)

Performance (as tested by ITTS Inc. USA)

Stain Resistance Flammability Radiant Panel US Federal Flammability Std **Pill Test** Smoke Density Colourfastness to light to wet & dry cleaning to ozone

Warranties

10 Year Carpet Wear Warranty Lifetime Antishock Carpet Warranty

Ideal for Heavy Commercial Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant **must** be used for all such installations. Due to dyelot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet

Suitability Installation Instructions Heavy domestic - Light Commercial Underlay and Gripper Rods

UC FLOOR Elegance & Comfort in Modern Living