

## LABELLE







3606 RAFFLES



3607 NOVOTEL



3608 ORCHARD



3609 FURAMA



3610 ESPLANADE



3611 ASCOTT



**5131 FAIRMONT** 



5132 STAMFORD



**5133 BAYVIEW** 



5134 SOFITEL



5135 FULLERTON



5136 WESTIN












6902 MANDARIN



6903 TRADERS



6904 CARLTON



**6905 REGIS** 



6906 PENINSULA



7001 CONCORDE



7002 BROADWAY



7003 FORTUNA



7004 SEDONA



7005 MARRIOT



7006 INTERCON







## **LABELLE Specifications**

Construction

Yarn Composition

Pile Weight

Total Weight

Total Height

Ca. 1085 g/m² (32 oz/yd²)

Ca. 1870 g/m² (55.14 oz/yd²)

Ca. 6.5 mm (+/- 0.5 mm)

Ca. 8.5 mm (+/- 0.5 mm)

Pensity

Pilonary Racking

PR Woven Cloth

Primary Backing PP Woven Cloth Secondary Backing ActionBac® Standard Roll Size 3.66 m x 30 m

## Performance (as tested by ITTS Inc. USA)

Stain Resistance 3 (AATCC-175-2003), 3M Scotchguard Treatment

Static Control Built-in Permanent
Tuft Bind 5.4 lbs (ASTM-D-1335)

Dimensional Stability Pass - Max. 0.2% change (AACHEN)
Flammability
Radiant Panel Pass - Class II (ASTM-E-648)

Pill Test Pass - 8 (ASTM-D-2859-06)
US Federal Flammability Std Pass (GB20286-2006/Cf1-S1 T0),
(ASTM-D-2859-96)

Smoke Density Pass - Max. 450 (ASTM-E-662-06) Colourfastness

to light Excellent - 5 (AATCC-16E)
to wet & dry cleaning Excellent - 5 (AATCC-165)
to ozone Excellent - 5 (AATCC-129)
Indoor Air Quality CRI Green Label Plus No. GLP1350

## Warranties

10 Year Commercial And Hospitality Carpet Wear Warranty Lifetime Antishock Carpet Warranty

Ideal for Medium and Heavy Hospitality use in Hotel Suite Rooms, Hotel Corridors, Offices, Restaurants, Retail Outlets, etc

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant **must** be used for all such installations. Due to dye lot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.





