



UC FLOOR

ROYAL AXMINSTER



102 GRAPHITE GREY

CUT PILE PATTERNED

Please note: There may be slight color difference between the picture and actual carpet.



328 EMERALD GREEN



549 GARNET RED



102-GRAPHITE GREY



212-HARMONIC BEIGE



328-EMERALD GREEN



431-PERSIAN BLUE



549-GARNET RED

ROYAL AXMINSTER Specifications

Construction	Cutpile Axminster
Yarn Composition	80% NZ & UK Wool, 20% Nylon 6.6
Pitch per inch	7
Rows per inch	8
Pile Weight	Ca. 1152 g/m ² (34 oz/yd ²)
Total Weight	Ca. 1850 g/m ² (54.5 oz/yd ²)
Pile Height	Ca. 7 mm (+/- 0.3 mm)
Total Height	Ca. 9 mm (+/- 0.3 mm)
Yarn Count	R660 Tex / 2ply
Warp	Cotton & Polyester
Weft	PP Backing
Latex	Fray Resistant Latex Compound
Standard Roll Size	4 m x 25 m
Pattern Repeat	40 cm x 51.4 cm

Performance (as tested by ITTS Inc. USA)

Carpet Classification	BS7131
Fire Classification	BC EN ISO 13501-1:2002
Flammability	BS4790
Abrasion Resistance	PD 6527:method 17:1990
Dimensional Stability in water	BS4682
Color Fastness to sea water	BS EN ISO105-E02:1996
Thickness loss under Static loading	BS 4939:1987 (2003)
Thickness loss under Dynamic loading	BS ISO 2094:1999 (2005)
Tuft withdrawal force	BS 5229:1975 (2003)
Tensile Strength	BS EN ISO 13934-1:1999
Non-Hazardous: AZO Dyes	EN14361-1
Non-Hazardous: 4 Aminazobenzene	EN14361-1

Suitability

For Public Areas, Corridors, Guest Room, Restaurant, Casino, VIP Lounge, Staircase etc. Inherently Colorfast and Stain Resistant.

Warranties

10 Year Carpet Wear Warranty
Lifetime Antishock Carpet Warranty

Ideal for Medium Contract Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant **must** be used for all such installations. Due to dye lot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.



ROYALAXMINSTER