

ROYAL TOUCH







311 BORDEAUX



329 AMAZON



333 NOUGAT



336 CAMEL



343 BISTRO



354 GOLD LEAF



374 BLUE STONE



380 COGNAC



392 GRANITE



395 SMOKE











Manufactured in Belgium

ROYAL TOUCH Specifications

1/10" Gauge Cut Pile Construction 100% Super Soft iSENSE® Nylon Yarn Composition Pile Weight Ca. 2400 g/m² (70 oz/yd²) Total Weight Ca. 2760 g/m² (81.39 oz/yd²) Ca. 13 mm (+/- 0.5 mm) Pile Height Total Height Ca. 15.5 mm (+/- 0.5 mm) Backing FusionBac® Tufts per sqm 286,375/m² Standard Roll Size 3.98 m x 22 m

Performance

Fire Classification C_{ff}-s1 0.21 Thermal Resistance In m²C°/W DL_w = 34 dB 1008#BL0001 Sound Absorption DOP

Warranties

10 Year Residential Carpet Wear Warranty Lifetime Antishock Carpet Warranty

Ideal for Bedroom, Living Room, Dining Room, Entrance, Hallway, Study Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant \boldsymbol{must} be used for all such installations. Due to dye lot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.

