



UC FLOOR

ROYAL WELCOME



310 YELLOW

CUT PILE SOLID COLOR


Please note: There may be slight color difference between the picture and actual carpet.



310 YELLOW




414 CINNAMON



427 RED



442 KHAKI



457 ORIENTAL BLUE



494 CHAMPAGNE



495 ALMOND BEIGE



496 PEACH TAN



723 POODLE GREY



427 RED

ROYAL WELCOME Specifications

Construction	1/8" Tufted Cut Pile
Yarn Composition	100% Solution Dyed Heatset Polypropylene
Pile Weight	Ca. 900 g/m ² (26.5 oz/yd ²)
Total Weight	Ca. 1700 g/m ² (50 oz/yd ²)
Pile Height	Ca. 8 mm (+/- 0.5 mm)
Total Height	Ca. 9 mm (+/- 0.5 mm)
Stitch Rate	33 per 10 cm
Density	138,600/m ²
Standard Roll Size	3.66 m x 30 m

Performance (as tested by ITTS Inc. USA)

Stain Resistance	10 (AATCC-175-2003)
Static Control	Pass
Tuft Bind	Pass - 3.1 lbs/y ³ (ASTM-D-1335)
Flammability	
US Federal Flammability Std	Pass (CPSC FF-1-70)
Pill Test	Self-extinguishing (ASTM-D-2859)
Smoke Density	Pass - Max. 450 (ASTM-E-662-06)
Colourfastness	
to light	Excellent - 5 (AATCC-16E)
to wet & dry crocking	Excellent - 5 (AATCC-16S)
to Ozone	Excellent - 5 (AATCC-129)

Warranties

10 Year Residential Carpet Wear Warranty
Lifetime Antishock Carpet Warranty

Ideal for Residential, Hospitality and Light Commercial Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant **must** be used for all such installations. Due to dye lot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.

Manufactured in U.A.E

ROYALWELCOME